



# 塑筋风电硅胶管 SP90

## Plastic reinforced wind power silicone hose SP90



### 材料结构：

内外管：蓝色工业级硅胶，表面布纹，颜色支持定制

增强层：螺旋塑筋 + 二层聚酯纤维编织布

### Material structure:

Inner and outer tubes: blue industrial grade silicone, surface texture, color support customization

Reinforcing layer: Spiral plastic reinforcement + Two layer polyester fiber woven fabric

### 尺寸规格：

内径：Ø13mm--102mm (支持定制)

标准长度：10M

工作温度范围：-60°C / +180°C

### Dimensions:

Internal diameter : Ø13mm---159mm (Support customization)

Standard length : 10M

Length operating temperature range : -60°C / +180°C

### 适用流体类型

### Applicable fluid type



### 产品应用：

该管柔软，耐撕裂，抗老化，正常使用，寿命极长。常被广泛用在风电行业中，主要被用于风力网轮机系统中抽吸和输送防冻液等。


### Product application:

The tube is soft, tear resistant, anti-aging, normal use, and extremely long service life. It is often widely used in the wind power industry, mainly used in the suction and delivery of anti-Dongye in the wind turbine system.

## Industrial silicone hose

### 产品优势

### Product advantages



耐高低温



大口径



抗高压



耐负压



抗氧化



弯曲性好



易清洗



支持定制

品名	内径 INNER DIA		壁厚 WALL THICKNESS +/- <sub>0.8</sub> mm	拆弯半径 BEND RADIUS (mm)	工作压力 WORK PRESSURE		爆破压力 BURST PRESSURE		标准长度 LEGNTH 米/根	真空气度 VACUUM
	(mm)	(inch)			Bar	psi	Bar	psi		
SP90-013	13	1/2	6	65	14.0	203	42.0	609	10	-0.7
SP90-019	19	3/4	6	90	13.0	188.5	39.0	565.5	10	-0.7
SP90-025	25	1	6	113	11.0	159.5	33.0	478.5	10	-0.7
SP90-032	32	1-1/4	6	180	9.0	130.5	27.0	391.5	10	-0.7
SP90-038	38	1-1/2	6	194	7.0	101.5	21.0	304.5	10	-0.7
SP90-051	51	2	6	270	6.0	87	18.0	261	10	-0.7
SP90-063	63	2-1/2	6	390	5.0	72.5	15.0	217.5	10	-0.7
SP90-076	76	3	6	450	3.5	50.75	10.5	152.25	10	-0.7
SP90-089	89	3-1/2	6	600	2.5	36.25	7.5	108.75	10	-0.7
SP90-102	102	4	6	790	2.0	29	6.0	87	10	-0.7